



GUARD REFRIGERANTE ORGÁNICO XT3 50% / GUARD COOLANT OAT XT3 50%

Description

Ethylene glycol-based engine coolant. With added fully organic inhibitors (OAT) that offer good protection against corrosion in all metals. Suitable for all types of cooling circuits (aluminium, copper, cast).

Properties

Product designed for direct use as it contains water treated to prevent hazards due to the formation of calcareous deposits and to prevent corrosion.

Its thermal characteristics enable good engine cooling without the fluid boiling.

Compatible with the metals and alloys present in cooling circuits: aluminium, copper, cast, brass and the most modern alloys.

Environmentally friendly: does not contain nitrites, amines, phosphates (NAP free) nor silicates.

Compatible with joints, seals and paints.

Quality levels, approvals and recommendations

- ASTM D1384
- ASTM D3306
- BS 6580:2010
- MB 325.3 (concentrado)
- MB 326.3 (diluido)

Technical specifications

	UNIT	METHOD	VALUE
Colour	-	Visual	Blue
Density at 20 °C	g/cm3	DIN 51757-4	1.065
Freezing point	°C	ASTM D1177	-35
pH a 20 °C	-	ASTM D1287	8

The above mentioned characteristics are typical values and should not be considered product specifications.